

Low Cost Sonobuoy Receiver (LCSR)

Light-weight, 19 inch rack-mountable receiver



Key features

- 19 inch, 1U rack size
- 1, 2, or 4 receive channels
- Digital output & control via Ethernet
- Analog & digital sonobuoy reception
- On-channel signal strength indicator
- UHF downlink exciter
- Sonobuoy position data

Overview

The LCSR is a low-cost solution for reception and remote control of sonobuoys. The receiver's on-board signal capture, demodulation, signal quality monitoring, and output data formatter provide stand-alone capability which only requires the user's personal computer to configure the receiver and capture the acoustic data. This allows the user's processing resources to be focused on data analysis.

The receiver is capable of analog (FM) and digital (FSK and GFSK) reception. Custom modulation types and data formats can be supplied on request. The LCSR includes front end out of band filtering for strong signal handling to support operation in the highly congested VHF band. Additionally, the receiver can provide power to an external preamplifier. A single Ethernet connection is used for all receive channel data outputs, receiver control, sonobuoy position data, and downlink commands.

Technical Specification

Ordering Information

90211A-801	1 channel LCSR
90211A-802	2 channel LC
R90211A-804	4 channel LCSR

Included Items

Receiver & power cord
 User's manual & Interface Description Document (IDD)
 Receiver control & command generator software
 Sample TCP packet parsing software

Mission Critical Accessories

Transit case
 50 W UHF RF power amplifier
 Mast mountable VHF pre-amplifier
 Software, real-time monitoring package (future item)

Rear Connections

VHF Receiver	Type-N (F) 50 ohm
UHF Exciter	Type-TNC (F) 50 ohm
Ethernet	RJ-45 (F)
Sync In/Out	BNC (F)
Tx Key Out	BNC (F)

Environmental

Operating Temp	+32°F to +122°F 0°C to +50°C
Shock/Vibration	Laboratory Grade

Performance

Channels	1, 2 or 4
Frequency range	136-173.5 Mhz
FM sensitivity	-85 dBm (typical) -105 dBm (typical) with preamp
Digital data rate	Up to 320 Kbps
Sample rate	Selectable
Output format	CFS or SG-90
Output level	0 dBm

Analog Sonobuoys

Compatible with legacy SSQ-36, SSQ-53, SSQ-62, and SSQ-101
 5 Hz - 40 KHz bandwidth reception in analog receive mode

Digital Sonobuoys

Compatible with SSQ-53G, SSQ-113, SSQ-101B, & SSQ-125A
 Supports legacy & NATO SG-90 formats
 Digital receive mode can support generic FSK/GFSK reception

Power Requirements

Power input	110 VAC 50-60 Hz
Power consumption	<30 Watts



Physical Specifications

Physical Description	1U, 19 inch rack mountable
Dimensions	1.875H x 19W x 17D (in) 4.76H x 48.26W x 17.18 (cm)
Weight	8.65 lbs / 3.92 kg (1 channel - add 0.83 lbs / 0.37 kg per channel)



+1 902 466 7491
 sonobuoys@umaritime.com
 umaritime.com

90211A-PDS-LCSR Rev B